



## EF3000iSE

Get the power you need for anything from a coffee-maker to a circular saw - in compact, user-friendly form. The EF3000iSE offers a 3.0 kVA capacity and maximum running time of over 20 hours at  $\frac{1}{4}$  rated load in Economy Control mode.

### Pure power on wheels.

Despite its sizeable power, the EF3000iSE has a whisper-quiet, low running sound of just 51\* dB (A) - and because it's mounted on four wheels, moving the generator around couldn't be easier.

And the smart throttle's load-sensing control automatically adjusts the engine speed to match the load, for greater fuel efficiency and noise reduction. \* at  $\frac{1}{4}$  rated load from 7 meters.

## EF3000iSE - BITNE KARAKTERISTIKE

### Inverter system with Pulse Width Modulation

This industry-leading system produces high-quality, clean electricity. Its pure sine wave is as clean as or cleaner than commercial power, making it suitable for products with built in microcomputers.

### Noise Block™ acoustically designed sound reduction system

This design uses sound absorbing material in key internal locations. Combined with the special muffler and molded fan, this ensures unbeatable noise reduction.



### Smart Throttle™ load-sensing throttle control

Smart Throttle automatically adjusts engine speed to precisely match load, for greater fuel efficiency and noise reduction



### 12V DC output

A handy output lets you recharge 12V batteries for use in recreational vehicles, car or marine products.

### Oil Watch warning system

To prevent engine damage and costly repairs, and enhance long-term durability, the generator automatically shuts off when oil begins to run low. It cannot be re-started until oil is added.

# EF3000iSE - TEHNIČKA SPECIFIKACIJA

## Motor

<b>Displacement</b>	171cc
<b>Maximum power output</b>	4.0 kW / 4000 rpm
<b>Starting system</b>	Electric and recoil

## Dimenzije

<b>Overall length</b>	680 mm
<b>Overall width</b>	445 mm
<b>Overall height</b>	555 mm
<b>Weight (kg)</b>	68kg
<b>Oil tank capacity</b>	0.6litre
<b>Fuel tank capacity</b>	13.0litres
<b>Noise level (LWA)</b>	88.0dB (A)
<b>Noise level 7 m</b>	51.0-57.0 dB (A) (*Economy Control on)

## Generator

<b>Generator type</b>	Inverter-Silent
<b>Frequency</b>	50 hz
<b>Rated AC output</b>	2800 VA
<b>Max AC output</b>	3000 VA
<b>Voltage AC</b>	230 V
<b>Rated current</b>	12.2 A
<b>DC output</b>	12/8V/A
<b>Power factor</b>	1
<b>Starter</b>	Direct
<b>Operating hours without refill</b>	8.0 - 20.5(*Economy Control on)